

Characterization of Turbulence Anisotropy, Coherence, and Intermittency at a Prospective Tidal Energy Site

Katherine McCaffrey^{1,2}, Baylor Fox-Kemper^{2,3}, Peter E. Hamlington^{2,4}, Jim Thomson⁵

¹Department of Atmospheric and Oceanic Sciences, University of Colorado, Boulder, CO 80309, USA

²Cooperative Institute for Research in Environmental Sciences, Boulder, CO 80309, USA

³Department of Geological Sciences, Brown University, Providence, RI, 02912, USA

⁴Department of Mechanical Engineering, University of Colorado, Boulder, CO 80309, USA

⁵Applied Physics Laboratory, University of Washington, Seattle, WA 98105, USA



Questions and Method

How do we describe the turbulence that a tidal turbine will experience, with only a time series of observations at one location in space?

What are the physical characteristics – size, shape, frequency – of the turbulence?

Can we parameterize, or simply classify, turbulence without doing the full analysis of physical characteristics?

How well can we model these turbulent properties with a stochastic turbulence generator?

Using data from an acoustic Doppler velocimeter in Puget Sound, WA, we perform a detailed characterization of the turbulent flow encountered by a turbine in a tidal strait. These results will be useful for improved realism in modeling the performance and loading of turbines in realistic ocean environments.

Observations

Dates	Feb 17-21, 2011
Depth	22m
Sampling Frequency	32 Hz
Hub Height	4.7m
Hub Height Max. Velocity	1.8 m/s

The data used in this analysis were collected from an acoustic Doppler velocimeter (ADV) off Nodule Point in the Puget Sound (Thomson et al. 2012). For a more in-depth description of the sites and the data collection details, see Thomson et al. (2012).




Figure 1: Horizontal component of velocity for the 4-day observation campaign.

Turbulence Metrics

Turbulence Intensity: $I_u = \frac{\sigma_u}{\bar{u}} = \frac{\sqrt{u'^2 - \bar{u}^2}}{\bar{u}}$

Coherent Turbulent Kinetic Energy: $CTKE = \frac{1}{2} \sqrt{(u'v')^2 + (u'w')^2 + (v'w')^2}$

Turbulent Kinetic Energy: $TKE = \frac{1}{2} (\overline{u'^2} + \overline{v'^2} + \overline{w'^2})$

Anisotropy Tensor: $a_{ij} = \frac{\overline{u'_i u'_j}}{2k} - \frac{\delta_{ij}}{3}, k = \frac{\overline{u'_i u'_i}}{2}$

Anisotropy Magnitude

A new and improved metric for turbulence characterization and classification (McCaffrey et al, submitted):

1. Coordinate-system invariant
2. Units of energy
3. Built to be like CTKE which correlates with loads (Kelley et al 2000)
4. Includes anisotropy from shear stresses (from invariant, II – Lumley and Newman, 1977) and normal stresses (from k)

Anisotropy Magnitude:

$$A = k \sqrt{a_{ij} a_{ji}}$$

Physical Descriptors

Coherence – Autocorrelation, and Taylor and Integral Scales: Average Integral scale is ~10 sec, but some intervals stay correlated up to ~100 sec.

$$\rho(\tau) = \frac{u'(t)u'(t+\tau)}{u'^2}$$

$$\lambda = \sqrt{-2 \left[\frac{\partial^2 \rho}{\partial \tau^2} \right]^{-1}}$$

$$\Lambda = \int_0^\infty \rho(\tau) d\tau$$

Intermittency – Probability density function: Flow is more intermittent at time scales of ~30-60 sec, which correlate to ~3-6m by Taylor's hypothesis

Anisotropy – Barycentric Map from eigenvalues (λ_i) of the anisotropy tensor (Banerjee et al. 2007): Flow is not isotropic!

$$\begin{aligned} C_{1c} &= \lambda_1 - \lambda_2 \\ C_{2c} &= 2(\lambda_2 - \lambda_3) \\ C_{3c} &= 3\lambda_3 + 1 \end{aligned}$$

Parameterization

How do we represent how "turbulent" a location is?

Is I_u , CTKE, or A better at representing intermittency, coherence, and anisotropy?

	λ (sec)	Λ (sec)
I_u	0.596	0.450
TKE	0.747	0.079
CTKE	0.680	0.017
A	0.884	0.317

A best captures:

- Anisotropy from barycentric maps
- Intermittency from pdfs
- Coherence from the Taylor scale




Figure 2: Autocorrelation function from ADV data at Nodule Point, with the average.




Figure 3: Probability density function of velocity differences from ADV data at $\Delta t = 1/32s$ (black), and 3m (gray) and 6m (white) rotor diameters.




Figure 4: Barycentric map based on eigenvalues colored by A for the ADV data at Nodule Point.

Parameterization methods:

- Barycentric maps colored by 4 metrics
- Pdfs separated by strength of 4 metrics
- Regression performed on Taylor and Integral scales versus 4 metrics




Figure 5: A versus Taylor scale, λ , with regression for the ADV data at Nodule Point.




Figure 6: Autocorrelation from HydroTurbSim data, with the average.




Figure 7: Probability density function of velocity differences from HydroTurbSim data for $\Delta t = 1/10s$ (black), and 3m (gray) and 6m (white) rotor diameters.




Figure 8: Barycentric map from HydroTurbSim data colored by A.

Stochastic Model

Output from the National Renewable Energy Laboratory's HydroTurbSim model was analyzed to determine which aspects of the realistic flow a stochastic turbulence generator captures.

Input:

- Background mean flow profile
- Turbulent spectral density curve based on observations
- Turbulence intensity standard
- Reynolds Stresses

Method:

- Inverse fast Fourier transform
- Spatial correlation function

Output:

- Two-dimensional snapshots of three velocity components in time (or, assuming Taylor's hypothesis, the third dimension in space)

HydroTurbSim creates turbulence with a set turbulence spectrum, and defines anisotropy based on random-phase correlations between Reynolds stresses, and proportions between normal stresses.




Figure 9: Turbulence intensity, I_u , versus mean speed, colored based on A for HydroTurbSim data. Black dots are average I_u from ADV data.

Conclusions

Observational data results:

- Coherence was measured through autocorrelations, intermittency was measured through probability density functions, and anisotropy was measured based on the eigenvalues of the anisotropy tensor.
- Physical characteristics were parameterized by the turbulence intensity, turbulent kinetic energy, coherent turbulent kinetic energy, and anisotropy magnitude, which was introduced.
- A was shown to be the best at parameterizing coherence and anisotropy.

HydroTurbSim results:

- No coherent events are seen in the autocorrelation functions.
- Anisotropy is only captured when defined by the input (Reynolds shear stresses), but not the normal stresses, as seen in the pdf.
- HydroTurbSim does what it is built to do, but doesn't capture coherent events.
- LES is expected to capture the coherent structures that HydroTurbSim cannot.

Acknowledgements

Thanks are due to Levi Kilcher of the National Renewable Energy Laboratory for his input on the observations and for the HydroTurbSim model code. Also, the APL-UW staff for help in field data collection: Joe Talbert, Alex deKlerk, and Capt. Andy Reay-Ellers. And Brian Polagye (UW) and Marshall Richmond (PNNL) for experiment planning. JT was partially supported by DOE Northwest National Marine Renewable Energy Center. BF-K and PH are partially supported by NSF 1258907 and 0934737. KM is supported by the NOAA-ESRL/CIRES Graduate Research Fellowship.

References

- Banerjee, S., R. Krahl, F. Durst, and C. Zenger, 2007: Presentation of anisotropy properties of turbulence invariants versus eigenvalue approaches. *Journal of Turbulence*, 8 (32).
- Kelley, N., R. Osgrid, J. Balasiewicz, and A. Jablonowski, 2000: Using time-frequency and wavelet analysis to assess turbulence/rotor interactions. Tech. rep., 19th American Society of Mechanical Engineers Wind Energy Symposium.
- Lumley, J. and G. Newman, 1977: The return to isotropy of homogeneous turbulence. *Journal of Fluid Mechanics*, 82, 161-178.
- McCaffrey, K., B. Fox-Kemper, P. E. Hamlington, J. Thomson, 2013: Characterization of Turbulence Anisotropy, Coherence, and Intermittency at a Prospective Tidal Energy Site: Observational Data Analysis. *Renewable Energy*, submitted.
- Thomson, J., B. Polagye, M. Richmond, and V. Dargesh, 2012: Measurements of turbulence at two tidal energy sites in Puget Sound, WA. *Institute of Electrical and Electronics Engineers*, 37(3), 363-374.