

ALL ABOUT WATER LEVEL MONITORING

Obscape's Level Gauge delivers real-time water level measurements. It records the water level using a highly accurate radar sensor. Since the instrument is mounted above the water surface, deploying it in the field is easy.

The Level Gauge is suitable for application in natural as well as manmade water systems. Whether you are interested in tidal water level variations, stormwater runoff or storage basin volumes, the Obscape Level Gauge will suit your needs.



KEY FEATURES

- Accurate water level data
- Radar technology
- No underwater components
- Completely wireless
- Real-time data

- Solar poweredGSM telemetry (3G)
- Multiple mounting options
- Versatile data portal included

CONVENIENT WATER LEVEL MONITORING

Water level monitoring plays an important role in monitoring natural or man-made water systems. The Level Gauge is suitable for application in rivers, estuaries, canals, manholes and storage basins. The instrument measures the distance to the water surface using an industry-standard radar sensor. It is mounted above the water surface, which avoids costly and labour-intensive underwater operations. The 20 metre range of the Level Gauge will cover even the most extreme water level variations.

COMPLETELY WIRELESS

The Level Gauge is completely wireless. Power is supplied through built-in solar panels, while data are transmitted in real-time using a 3G GSM connection. Therefore, the Level Gauge is easy to install at any desired location within GSM coverage. There is no need to worry about access to mains power or router internet access. Its wireless nature makes the Level Gauge very suitable for monitoring of remote areas.

WWW.OBSCAPE.COM

Obscape B.V. | Reg.: 74971409 | VAT: NL860092550B01 Da Costalaan 26, 2281SH Rijswijk, The Netherlands | info@obscape.com

VERSATILE DATA PORTAL

The value of real-time observations strongly depends on the ability to view and analyse them in real-time. Therefore, the Level Gauge comes with a license for the Obscape Data Portal. The data collected by your Level Gauge, as well as the data from any other Obscape device you own, are collected into the Data Portal. The Data Portal offers various options for viewing, managing and downloading your water level data, including the generation of PDF reports. It is your ultimate tool to unify the office and the field.



A series of the series of t

TECHNICAL SPECIFICATIONS

DATA SPECIFICATIONS		
Water level, battery voltage, GSM signal strength, internal temperature		
Specified by the user in the Data Portal		
20 m		
2 mm		
5 – 60 minutes (user selectable)		
On-board micro SD card		

WEB-PORTAL SPECIFICATIONS		
REAL-TIME GRAPHS	Water level and additional (status) parameters	
DOWNLOADS	Raw data (CSV format), Graphs (PNG), Reports (PDF)	
FORWARDERS	JSON API or HTTP post	
STATUS NOTIFICATION EMAILS	Online/offline, battery level, water level threshold exceedance	

ELECTRICAL CHARACTERISTICS		
SOLAR PANEL	3W	
CAPACITY	310	
BATTERY	1 single 18650 lithium battery	
NOMINAL VOLTAGE	3.7 V	

TELEMETRY SPECIFICATIONS		
COMMUNICATION MODE	GSM (3G)	
REAL-TIME DATA	5 minutes – 24 hours (user selectable)	
REAL-TIME DATA	Water level and additional (status) parameters	
GSM DATA LOAD	Approx. 8 kB per message	

PRICING	
LEVEL GAUGE	€2,550 including web-portal license and mounting bracket
GSM COMMUNICATION	Micro SIM card and sufficient data credit to be arranged by user. Level Gauge can also be run in offline mode (data saved to SD card).

PHYSICAL CHARACTERISTICS	
HOUSING WIDTH	87 mm
HOUSING DEPTH	87 mm
HOUSING HEIGHT	280 mm
HOUSING WEIGHT	2 kg
RADAR SENSOR	InnoSenT iSYS-6003

Version: 1 N	1ay 2020
--------------	----------

WWW.OBSCAPE.COM

Obscape B.V. | Reg.: 74971409 | VAT: NL860092550B01 Da Costalaan 26, 2281SH Rijswijk, The Netherlands | info@obscape.com