

Forsta Filters Inc.

www.forstafilters.com

PO Box 6397,

Burbank, CA 91510

info@forstafilters.com

888.9-FORSTA

Ph: 310.837.7177

Fx: 310.837.6477



90 SERIES

The 90 Series offers a unique configuration of self-cleaning irrigation and industrial water filters.

90 Series self cleaning water filters have a right angle flange configuration that provides a compact filter unit. A 90 Series automatic water filter is much smaller than its 180 Series counterpart, and offers a space-saving alternative.

90 Series industrial water filters are ideal where large debris from source water is not a concern. These filtration systems house a single fine screen, and achieve specified water quality in one step.

These automatic water filters provide solutions in a wide variety of industrial, irrigation, and municipal applications

Filter Characteristics:

- Flow Rate: 15 – 1,600 gpm
- Flush cycle duration: 4 – 10 seconds
- Flush valve size: Single 1", 1.5", 2"
- Screen opening: 5μ – 4000μ
- Temperature: 150°F
- Flush Volume: 3 – 50 gallons per backwash
- Working pressure: 35 – 150 psi
- Material: Stainless Steel, Duplex, Super Duplex or FRP



90 SERIES SPECIFICATIONS

Filter Model	Screen Area (sq ft)	Max Flow Rate (gpm)	Connection Size (in)
M.75-90	0.4	50	0.75
M1-90	0.4	75	1
M1.5-90	0.4	100	1.5
M2-90	0.4	100	2
A1-90	1	75	1
A1.5-90	1	150	1.5
A2-90	1	200	2
A3-90	1	200	3
B2-90	2	200	2
B3-90	2	300	3
B4-90	2	400	4
C2-90	3	200	2
C3-90	3	300	3
C4-90	3	500	4
C6-90	3	600	6
C8-90	3	600	8
CL2-90	4	200	2
CL3-90	4	300	3
CL4-90	4	500	4

Filter Model	Screen Area (sq ft)	Max Flow Rate (gpm)	Connection Size (in)
CL6-90	4	800	6
CL8-90	4	800	8
CXL3-90	5	300	3
CXL4-90	5	500	4
CXL6-90	5	1000	6
CXL8-90	5	1000	8
CXL10-90	5	1000	10
D3-90	4.25	300	3
D4-90	4.25	500	4
D6-90	4.25	850	6
D8-90	4.25	850	8
E4-90	6.25	500	4
E6-90	6.25	1000	6
E8-90	6.25	1250	8
E10-90	6.25	1250	10
F4-90	8	500	4
F6-90	8	1000	6
F8-90	8	1600	8
F10-90	8	1600	10

90 SERIES INSTALLATION LAYOUT

